1085C Excavator

Service Manual

8-14930

CASE CONSTRUCTION

MidWestTech | Case 1085C Excavator Service Manual | Publication 8-14930

Order the manual at mid-west-tech.com >

1001

STANDARD TORQUE SPECIFICATIONS

TABLE OF CONTENTS

Torque Specifications - Decimal Hardware 1001-2

Torque Specifications - Metric Hardware ... 1001-3

Torque Specifications - Steel Hydraulic Fittings 1001-4

Torque Specifications - O-ring Face Seal Fittings 1001-5

CASE CORPORATION

Bur 8-71600

Printed in U.S.A.
Issued May 1988

MidWestTech | Case 1085C Excavator Service Manual | Publication 8-14930

Order the manual at mid-west-tech.com >

TORQUE SPECIFICATIONS - DECIMAL HARDWARE

Use the torques in this chart when special torques are not given. These torques apply to fasteners with both UNC and UNF threads as received from suppliers, dry, or when lubricated with engine oil. Not applicable if special graphites, molydisulfide greases, or other extreme pressure lubricants are used.

Grade 5 Bolts, Nuts, and Studs



Size	Pound-Feet	Newton metres
1/4 in	9-11	12-15
5/16 in	17-21	23-28
3/8 in	35-42	48-57
7/16 in	54-64	73-87
1/2 in	80-96	109-130
9/16 in	110-132	149-179
5/8 in	150-180	203-244
3/4 in	270-324	366-439
7/8 in	400-480	542-651
1.0 in	580-696	787-944
1-1/8 in	800-880	1085-1193
1-1/4 in	1120-1240	1519-1681
1-3/8 in	1460-1680	1980-2278
1-1/2 in	1940-2200	2631-2983

Grade 8 Bolts, Nuts, and Studs



Size	Pound-Feet	Newton metres
1/4 in	12-15	16-20
5/16 in	24-29	33-39
3/8 in	45-54	61-73
7/16 in	70-84	95-114
1/2 in	110-132	149-179
9/16 in	160-192	217-260
5/8 in	220-264	298-358
3/4 in	380-456	515-618
7/8 in	600-720	814-976
1.0 in	900-1080	1220-1465
1-1/8 in	1280-1440	1736-1953
1-1/4 in	1820-2000	2468-2712
1-3/8 in	2380-2720	3227-3688
1-1/2 in	3160-3560	4285-4827

NOTE: *Use thick nuts with Grade 8 bolts.*

811360B

Order the manual at mid-west-tech.com >

TORQUE SPECIFICATIONS - METRIC HARDWARE

Use the following toques when special torques are not given.

These values apply to fasteners with coarse threads as received from supplier, plated or unplated, or when lubricated with engine oil. These values do not apply if graphite or molydisulfide grease or oil if used.

Grade 8.8 Bolts, Nuts, and Studs

8.8

Size	Pound-Feet	Newton metres
M4	2-3	3-4
M5	5-6	6.5-8
M6	8-9	10.5-12
M8	19-23	26-31
M10	38-45	52-61
M12	66-79	90-107
M14	106-127	144-172
M16	160-200	217-271
M20	320-380	434-515
M24	500-600	675-815
M30	920-1100	1250-1500
M36	1600-1950	2175-2600

Grade 10.9 Bolts, Nuts, and Studs

10.9

Size	Pound-Feet	Newton metres
M4	3-4	4-5
M5	7-8	9.5-11
M6	11-13	15-17.5
M8	27-32	37-43
M10	54-64	73-87
M12	93-112	125-15
M14	149-179	200-245
M16	230-280	310-380
M20	450-540	610-730
M24	780-940	1050-1275
M30	1470-1770	2000-2400
M36	2580-3090	3500-4200

Grade 12.9 Bolts, Nuts, and Studs


12.9


Usually the torque values specified for grade 10.9 fasteners can be used satisfactorily on grade 12.9 fasteners.

811359A

Order the manual at mid-west-tech.com >

THROTTLE INTERLOCK, BACKUP ALARM, TURNTABLE ANGLE SWITCH, TRANSMISSION SHIFTER, TRANSMISSION SOLENOIDS, TRANSMISSION RANGE, AXLE OSCILLATION LOCK, PARKING BRAKE, HYDRAULIC INTERLOCK, AND DIODE MODULES





Bur 8-14850

Issued 5-90 Printed in U.S.A.

Order the manual at mid-west-tech.com >